

Wells-Index Division

A&D Machinery Company
701 West Clay Ave. Muskegon, MI 49440 USA
Phone 231/759-0950 Fax 231/728-7456
wellsindex@aol.com www.wellsindex.com



Some of the features that make our Model 847 a better machine.

847

Sliding lever for quick speed changes

Lets the operator change RPM quickly
no tedious turning of the crank

5/8 inch diameter head mounting bolts

Quill downfeed rated for a 5/8 inch dia. drill

We use gears and shafts 2 to 3 times larger that are
supported by ball bearings

Downfeed can be used at any RPM

Table 3 1/8 inches thick

No loss of travel when power feed installed

Parts and service available for all 847's made

Parts and service for all our machines made since 1940
Most imports change so often parts are not available 7 yrs later

3 hp constant duty Baldor spindle motor

Quality cast iron poured in the USA

10 spline 1.25" dia spindle shaft mounted on

2 pair of precision angular contact bearings

Competition

Small handwheel

1/2 inch diameter

3/8 diameter drill

3000 rpm or less

2 3/4 inches ?

??????

??????

??????

?????

6 spline 1.0" dia mtd on

1 pair and a single row

WELLS-INDEX YOUR SOURCE FOR QUALITY USA MADE KNEE MILLS